

# USER'S MANUAL

Thank you for purchasing this PIVOT product.  
Please read this manual carefully and keep it for future reference.

- If this product is given to another user, make sure to include this User's Manual.



## Please check the contents of the package



Insert Holder



Cushion Tape



Cushion Gum



User's Manual (This Book)

Designed for **BRZ & 86 Aqua**

Install meters listed below;

- DUAL GAUGE
- MULTI GAUGE (X2R/ X2C)

## Installing the Insert Holder

(Illustrations are of 86 & BRZ)

### 1 Pulling out the air vent

■ = Place of hook

### 2 1. Affix the supplied Cushion tape or Cushion Gum to the Insert holder

3 places  
For 86 & BRZ

4 places  
For Aqua

Cushion tape / Cushion Gum

### 2. Decompose the air vent and replace the Air vent part C to the Insert Holder

Air vent part A

Air vent part B

Air vent part C

Air vent part D

Replace

### 3 Make a hole on fan duct if necessary, and put through the cable

10mm or more

Size of the hole

6mm or more

### 5 Affix Cushion tape to the base of the meter and connect the 4-pin connector through out the air vent at 4. Then press into the Insert Holder combined with the air vent.

Cushion Tape (3 places)

4-pin Connector

### 4 Pull the cable through the hole from the back side of the air vent, then return the air vent to its original position

Pull the cable from back side of the air vent

4-pin Connector

Fan duct

Through the hole

### 6 Install Completed